



SQ 8700

MASS SPECTROMETER

The SCION 8700 (SQ) GC-MS is designed for today's fast paced analytical laboratory. Innovative design features such as a Lens-Free ion path, heated ion optics and an Extended Dynamic Range (EDR) detector enable the SCION SQ to deliver accurate quantification and identification on a routine basis, even in complex matrices.



SCION 8700 SQMS

THE SCION 8700 SQMS HAS A SMALL FOOTPRINT BUT DOES NOT COMPROMISE ON QUALITY.

The SCION 8700 SQMS is the chromatographer's choice for quadrupole mass detection, designed to match your most stringent needs for analytical performance and productivity.

The SCION 8700 SQMS offers superior sensitivity and robustness based on innovative ion optics, and fast and easy methods development.

Coupled to our outstanding GC instruments, the SCION 8700 SQMS system defines a new standard of usability for routine analysis

Available in three models, the SCION 8700 SQMS offers a flexible solution for any laboratory.

Software



SCION MS Workstation for data acquisition, data handling and reporting.




Optional Spectral Libraries: NIST, Wiley, and Pfleger/ Maurer/ Weber (PMW) libraries with user customisable libraries and automatically searching of multiple libraries.



Autotune in all ionisation modes, special tunes for EPA methods (DFTPP/BFB).

An Innovative Solution

- An innovative lens-free ion path delivers simplified tuning
- The dual filament source increases uptime
- The high capacity (400L) turbopump allows the fastest pump down speed on the market
- Hydrogen carrier approved



Primed for Sensitivity



Primed for Sensitivity


- He in q0 (active-focusing) for added sensitivity in routine applications
- Premium Focusing Curved Q0 Ion optics has a 90° angle that aids the elimination of neutrals
- Ability to handle fast GC analysis- up to 25 ml/min column flow rates
- The SCION 8700 includes the **best-in-class** high performance turbo pump for worry-free operation
- Ideal for routine environmental analysis, especially purge-and-trap applications (pumps away potential water interference)



Extended linear range


- **Extended Dynamic Range** mode ensures you have **optimal** detection in **every** scan for trace components within complex mixtures.
- When detector approaches saturation, the system **automatically lowers** the multiplier voltage, always ensuring optimal detection of components, even if they co-elute.
- Easily analyze complex mixtures that contain both **trace** residues as well as compounds **of high abundance** in the **same run**.

Active-focusing q0



SIM of Hexachlorocyclopentadiene

Up to six orders of magnitude





Premium Flexibility



8700 Premium is EI and CI Ready

- Heated q0 for the ultimate in robust 24/7 operation
- Ultra-sensitive Negative Chemical Ionization (NCI) detection
- Ability to handle fast GC analysis- up to 25 ml/min column flow rates
- SCION Premium is CI ready and easily converts from the EI standard source.
- NCI applications such as pyrethroids are easily set up using Compound Based Scanning (CBS).



| COMPOUND | RT | RT WINDOW | SCAN TYPE | SCAN TIME (MS) | POLARITY |
|--------------|-------|-----------|-----------|----------------|----------|
| Resmethrin | 17.35 | 0.50 | SIM | 100 | Neg |
| Resmethrin 2 | 17.58 | 0.50 | SIM | 100 | Neg |
| Bifenthrin | 18.56 | 0.50 | SIM | 100 | Neg |
| Fenpropatrin | 18.74 | 0.50 | SIM | 100 | Neg |



GC Compatibility

The SCION SQMS series interface seamlessly with SCION Gas Chromatograph (SCION **8300** and **8500** Model GC)

- Injectors: Split/Splitless (SSL), Programmable Temperature Vaporisation (PTV) and PTV with back-flush (PTV/BF), Cold On-Column (COC)
- Autosamplers: 8400 Pro; 8410 Pro; CTC PAL COMBI-xt
- GC Oven Temperature: Ambient+4°C to 450°C, -100°C to 450°C (with Liquid N₂); -60°C to 450°C (with Liquid CO₂)
- Temperature Ramps/Holds: 24/25
- Pneumatic: Electronic Flow Control (EFC) or Manual
- ChromatoProbe: Direct introduction of solids, liquids or slurries (requires PTV injector)



SCION 8300 GC coupled to the 8700 SQMS



SCION 8700 SQMS Series

Model Range

| SQ 8700 MODELS | FEATURES | BENEFITS/APPLICATIONS |
|------------------------|--|--|
| SCION SQ Select | <ul style="list-style-type: none"> • EI only • Select q0 • (300/400 L/s) Turbo Pump | <ul style="list-style-type: none"> • Routine |
| SCION SQ Premium EI | <ul style="list-style-type: none"> • EI only • Active-Focusing q0 • Ultra-High Performance Split-flow (300/400 L/s) Turbo Pump | <ul style="list-style-type: none"> • High-Sensitivity • Fast pump-down |
| SCION SQ Premium EI/CI | <ul style="list-style-type: none"> • CI ready • Active-Focusing 'premium' q0 • Ultra-High Performance Split-flow (300/400 L/s) Turbo Pump | <ul style="list-style-type: none"> • Ultimate flexibility • CI • Pos/Neg detector |

Performance specifications

| MODE | TEST* (SSL INJECTOR IN HOT SPLITLESS MODE) | SPECIFICATION† |
|----------------------------|---|----------------|
| EI Full Scan | 1pg Octafluoronaphthalene (OFN) from m/z 50-300 for m/z 272 | S/N ≥ 1,500:1 |
| PCI Full Scan ^Δ | 100pg Benzophenone (BZP) from m/z 80 to 230 for m/z 183 | S/N ≥ 600:1 |
| NCI Full Scan ^Δ | 200fg OFN from m/z 200 to 300 for m/z 272 | S/N ≥ 1000:1 |

* All tests performed with helium at carrier gas

† The Signal-to-Noise ratio S/N values are based on RMS

Δ CI tests use methane as reagent gas

Physical Specifications

Dimensions (H x W x D) and Weight

- 45cm (18in) x 28cm (11in) x 57cm (22.5in)
- 37kg/82lb

Additional space should be added for the data system, monitor and printer.

SCION Instruments Contact Details:

[Contact Us](#) | [SCION Instruments](#) | [Gas Chromatography Solutions](#)

Find your SCION Instruments Distributor in your Region or Country:

[Distributors](#) | [SCION Instruments](#) | [Gas Chromatography Solutions](#)

Read more about the SQMS

[SCION TQMS](#) | [SCION Instruments](#)

Parts and Consumables

[SCION GC](#) | [SCION Instruments](#)

SCION Instruments UK Ltd.

4 Michaelson Square
Livingston,
EH54 7DP, Scotland,
United Kingdom

scioninstruments.com
Tel: +44 (0) 1506 300200
Email: sales-eu@scioninstruments.com

SCION Instruments NL BV

HQ, Amundsenweg 22-24,
4462 GP Goes,
The Netherlands

scioninstruments.com
Tel: +31 (0) 113 287 600
Email: sales-eu@scioninstruments.com

SCION Instruments USA

11840 West Market Place
Suite K and L,
Fulton, MD 20759
North America

scioninstruments.com
Tel: +1-844-547-0022
Email: sales-USA@scioninstruments.com